Quantum <mark>Design</mark>



Service Note 1014-301

Quantum Design's Printer Recommendations

The following printers have been qualified on a computer running the Windows XP Pro operating system and the latest released MultiVu software on Quantum Design's SVSM, PPMS, MPMS, and VersaLab measurement platforms. Quantum Design recommends powering all your electronics from one circuit to prevent ground loops which can cause problems during measurements. To achieve this, we recommend using an external PDU to supply power to all the components. To do this a printer power cord must be purchased from an appropriate vendor. Quantum Design also recommends installing the most basic printer drivers on the computer to help maintain the system's performance. Please contact your local Quantum Design service representative if you have questions about the electrical power configuration for your system.

Canon PIXMA iP2600

Driver version: rev. 4.5.5.102 Input power: 100-240 VAC, 50-60 Hz Approximate printer weight (with cartridges): 3.7 kg (8.0 lbs) Recommended power cord: IEC-320 C-14 to IEC-320 C-7* Approximate printer dimensions, with tray extended: Width: 442 mm (17.4 in), Depth: 253 mm (10.0 in), Height: 142 mm (5.6 in)



Canon PIXMA iP3600

Driver version: rev. 4.6.0.101 Input power: 100-240 VAC, 50-60 Hz Approximate printer weight (with cartridges): 5.6 kg (12.2 lbs) Recommended power cord: IEC-320 C-14 to IEC-320 C-7 * Approximate printer dimensions with tray extended: Width: 431 mr

Approximate printer dimensions, with tray extended: Width: 431 mm (17.0 in), Depth: 296 mm (11.7 in), Height: 153 mm (6.0 in)



HP DeskJet 6988

Driver version: rev. 60.053.243.00 Input power: 100-240 VAC 50-60 Hz Approximate printer weight, without cartridges: 6.3kg (13.8 lbs) Recommended power cord: IEC-320 C-14 to IEC-320 C-7 * Approximate printer dimensions, with tray extended: Width: 450 mm (17.7 in), Depth: 432 mm (17.0 in), Height: 145 mm (5.7 in)



Kodak ESP 3

Driver version: rev.3.40.1208 Input power: 110-220VAC 50-60Hz Approximate printer weight: 5.9 kg (13.1 lbs) Recommended power cord: IEC-320 C-14 to IEC-320 C-5 * Approximate printer dimensions, without tray extended: Width: 422 mm (16.6 in), Depth: 298 mm (11.8 in), Height: 173 mm (6.9 in)



WHERE TO PURCHASE POWER CABLES:

Americord

290 W. 300 S Logan, Utah 84321 Tel.: (800)-647-6231 or (435)-752-9770 Fax: (435)-752-9737 Website: <u>www.americord.com</u>

International Wiring Devices and Cord Sets

P.O. Box 3374 Enfield, Connecticut 06083 Tel.: (860) 749-6380 Fax: (860) 749-2985 Website: www.internationalconfig.com

Interpower Corporation

P.O. Box 115 100 Interpower Avenue Oskaloosa, IA 52577 (USA) Tel.: (800) 662-2290 Fax: (800) 645-5360 Website: www.interpower.com